

# ICS Conference rooms C4, C5 and C7 - upper floor: Technical data



## Size/dimensions/capacities

- Internal dimensions Length x Width 26.00 m x 14.50 m
- Total floor space/exhibition area 390 m<sup>2</sup>
- Ceiling height/clearance height 4.53 m/3.47 m

Due to the flexible partition wall system the three conference rooms can be divided in max. 12 individual rooms.

	m <sup>2</sup>	••••			
C4	390	440	208	76	88
C4.1	125	120	48	28	40
C4.1.1	63	45	18	20	22
C4.1.2	61	44	24	20	22
C4.2	133	120	48	28	40
C4.3	132	120	48	28	40
C4.1 + C4.2	258	280	128	52	64
C4.2 + C4.3	266	280	125	56	64

These capacities also apply to C5 and C7.

## Delivery to rooms

- Access via the ICS foyer
- Delivery via the delivery areas of C1 or C2
- Transport to upper floor via two freight elevators, permitted weight up to 4,000 kg each
- Dimensions of freight elevators (DxW) 3.20 m x 4.00 m

## Room specifications

- Barrier-free access
- Dimmable lights
- Daylight
- Control panel for room lighting/black-out option
- Black-out option with Venetian blinds
- Air-conditioning
- Type of floor
- Floor loading capacity
- Sound-insulated partition walls
- One side of room is glazed

carpet  
500 kg/m<sup>2</sup>

## Technical equipment and communication

- sound system
- control rooms in C4 and C7
- One monitor at each access to the rooms
- Beamer
- Projection surface in separable room
- Telecommunication connections
- High-voltage connection on request



This plan also applies to C5 and C7.

