

ICS Conference area C6 - upper floor: Technical data



Size/dimensions/capacities

Internal dimensions Length x Width

- C6.1 13.50 m x 14.50 m
- C6.2 (can be divided) 12.00 m x 14.50 m
- Foyer C6 14.40 m x 8.50 m
- Total floor space 582 m²
- Ceiling height/clearance height 4.53 m/3.47 m

Due to the flexible partition wall system room C6.2 can be divided in two individual rooms.

	m ²	●●●●	●●●●●	□□□□	□□□□
C6.1	205	200	96	40	52
C6.2	175	180	80	36	48
C6.2.1	89	81	30	28	32
C6.2.2	89	72	30	26	28
Foyer C6	122	--	--	--	--

Delivery to rooms

- Access via the ICS foyer
- Transport to upper floor via two freight elevators, permitted weight up to 4,000 kg each
- Dimensions of freight elevators (DxW) 3.20 m x 4.00 m

Room specifications

- Barrier-free access
- Dimmable lights
- Daylight
- Control panel for room lighting/black-out option
- Black-out option with Venetian blinds
- Air-conditioning
- Type of floor carpet
- Floor loading capacity 500 kg/m²
- Room C6.2 has sound-insulated partition walls
- One side of room C6.2 is glazed
- Room C6.1 has access to the foyer and is glazed on two sides

Technical equipment and communication

- Sound system
- One monitor at each access to the rooms
- Beamer
- Projection surface
- Telecommunication connections
- High-voltage connection on request

