

ICS Seminar rooms C3 and C8 - upper floor: Technical data



Size/dimensions/capacities

- Internal dimensions C3.1 and C8.1 (LxW) 7.70 m x 5.46 m
- Interior dimensions C3.2 and C8.2 (LxW) 6.52 m x 5.46 m
- Ceiling height/Clearance height 4.50 m/3.80 m

	m ²	••••			
C3.1	42	32	12	12	16
C3.1.1	25	18	--	--	6
C3.1.2	17	12	--	--	6
C3.2	34	28	12	12	16
C3.2.1	17	12	--	--	6
C3.2.2	17	12	--	--	6
C3.3.1	18	--	--	--	8
C3.3.2	18	--	--	--	8
C8.1	41	28	12	12	16
C8.1.1	24	18	--	--	6
C8.1.2	17	12	--	--	6
C8.2	35	28	12	12	16
C8.2.1	17	12	--	--	6
C8.2.2	17	12	--	--	6

Delivery to rooms

- Access via the ICS foyer
- Delivery via the delivery areas of C1 or C2
- Transport to upper floor via two freight elevators, permitted weight up to 4,000 kg each
- Dimensions of freight elevators (DxW) 3.20 m x 4.00 m

Room specifications

- Barrier-free access
- Dimmable lights
- Daylight
- Control panel for room lighting/black-out option
- Black-out option with Venetian blinds
- Air-conditioning
- Type of floor carpet
- Floor loading capacity 500 kg/m²
- Sound-insulated partition walls
- One side of room is glazed
- Partly equipped with sideboard (HxWxD) 1.10 m x 1.60 m x 0.44 m

Technical equipment and communication

- No fixed conference technology available.
- One monitor at each access to the rooms
 - Telecommunication connections

